



M mindman



AIR UNIT

ชุดกรองลมและจ่ายน้ำมัน



MACT300



Specification

Model	MACT300	
Components	MAF300, MAR301, MAL300	
Bore No.	8A	10A
Port size	1/4	3/8
Medium	Air	
Operating pressure range (*)	0.05~1 MPa	
Proof pressure	1.5 MPa	
Effective orifice	32mm ²	34mm ²
Regulated pressure range	0.05~0.85 MPa	
Ambient temperature	-5 ~+ 60°C (No freezing)	
Filter element	Standard: 5µm, Option: 40µm	
Lubricating oil capacity	55c.c	
Min. flow for oil drip	50 l/min	60 l/min
Recommended lubricating oil	Turbine oil ISO-VG32	
Attachment	Pressure gauge(PG-40), T-type bracket	
Weight	944g	

MACT400



Specification

Model	MACT400		
Components	MAF400, MAR400, MAL400		
Bore No.	8A	10A	15A
Port size	1/4	3/8	1/2
Medium	Air		
Operating pressure range (*)	0.05~1 MPa		
Proof pressure	1.5 MPa		
Effective orifice	24mm ²	35mm ²	40mm ²
Regulated pressure range	0.05~0.85 MPa		
Ambient temperature	- 5 ~+ 60°C (No freezing)		
Filter element	Standard: 40µm, Option: 5µm		
Lubricating oil capacity	200c.c		
Min. flow for oil drip	50 l/min	200 l/min	400 l/min
Recommended lubricating oil	Turbine oil ISO-VG32		
Attachment	Pressure gauge(PG-50), bracket		
Weight	2000g		